


X2-SERIES – RUGGED USB CONNECTIONS

USB C – JAM NUT RECEPTACLE WITH CORDSET X2-9876



INFORMATION

All dimensions in
mm (inch) unless
otherwise specified.

Mates with USB3CFTV

Shell derived from D38999

PN: X2-9876

Datasheet Version: 1.0

CATALOG:

Harsh Environment
Data Connectivity Solutions



Table A: Material & Plating

Material & Plating Code	Technical Design	ROHS-/REACH Compliant	Electrically Conductive	Salt Spray Resistance according to MIL spec.	Salt Spray Resistance according to VG spec.
V	Tin-Zinc grey Base material: Al-alloy Tin-Zinc over electroless Nickel	Yes	Yes	500 hrs	5 day cyclic
5	Electroless Nickel Base material: Al-alloy	Yes	Yes	48 hrs	n.a.
2	Zinc-Nickel black Coupling ring: Al-alloy, black anodized Shell: Zinc-Nickel black chromate over electroless Nickel	Yes	Yes	500 hrs	n.a.
6	Cadmium olive drab Coupling ring: Al-alloy, olive drab anodized Shell: Al-alloy Cadmium plated olive drab over electroless Nickel	No	Yes	500 hrs	5 day cyclic
9	Marine Bronze Base material: Marine Bronze CuAl10Ni5Fe4 (CW307G) Shotblast, nonreflective	Yes	Yes	n.a.	n.a.
1	Stainless Steel / passivated	Yes	Yes	n.a.	n.a.

Performance

Voltage Rating (V_BUS)	20 V
Current Rating (V_BUS)	5 A
Temperature	-20 °C to +85 °C
Mating cycles	>500
Type-C Receptacle	Pins A7&B7 and A6&B6 connected
Compatible with	USB 3.2 Gen 2

Table B: Cable length

Length Code	Length L in mm	Tolerance in mm
0500	500 (19.685)	+ 30 (1.181)
1000	1000 (39,370)	+ 40 (1.575)

Materials

Over molding (plug)	PVC
USB C	Nickel plated
Cable jacket	PVC
Cable type	UL 2725
Housing	See option material

For details about keyway polarization, USB C orientation and panel cut out see page 72-75 in the full „Harsh Environment Data Connectivity Solutions“ catalog.

How to order

	Table	X2-9876	11	5	N	0	0500
Basic part number							
Shell size							
Material & plating code	A						
Keyway polarization	5						
USB C orientation	9						
Cable length	B						

ORDER EXAMPLE

X2-9876-11-5 N 0-0500

USB C – JAM NUT

SIZE 11, ELECTROLESS NICKEL

KEYWAY = N (STANDARD)

USB C ORIENTATION = 0° (See drawing)

CABLE LENGTH 500 MM

EMCA CONNECTOR SOLUTIONS GMBH

X2-9876 | Datasheet Version 1.0

SALES@EMCA-CONNECTOR.DE

emca
connector solutions